

Specifications

SMART Room System[™] for Microsoft[®] Lync[®] for large rooms

Model SRS-LYNC-L

Overview


The SMART Room System™ for Microsoft® Lync® for large rooms features two SMART Board® 8070i-G4 interactive flat panels, a tabletop console, a high-definition camera, table microphones and speakers.

Using the installed Lync Room System software, you can start a meeting and connect with other individuals or meeting rooms with a single tap on the console or one of the interactive flat panels. You can write or draw on an interactive flat panel using the whiteboard feature, present a PowerPoint® slide show, connect a laptop to share its screen and share your content with connected individuals and meeting rooms in real time.




See smarttech.com/smartroom for more information on this product.

Dimensions and weights¹







 $^{^{1}}$ All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

For table microphones 30' (9 m) audio (interactive flat panel to table)

6' (1.8 m) USB Power

13' (4 m) audio (microphone to microphone)

	Weight	Shipping weight	Shipping dimensions
Interactive flat panel (×2)	205 lb. (93 kg)	251 lb. (114 kg)	77 1/8" × 56 1/4" × 15 3/8" (196 cm × 143 cm × 39 cm)
WM-SBID-501 wall mount (×2)	24 lb. (10.9 kg)	31 lb. (14 kg)	46" × 12 1/2" × 11" (117 cm × 32 cm × 28.1 cm)
Speakers	15 lb. (7 kg)	20 lb. (9.1 kg)	37 3/4" × 15 1/2" × 7 3/8" (96 cm × 39.5 cm × 18.8 cm)
System components	14 lb. (6.2 kg)	24 lb. (10.8 kg)	19 1/2" × 18" × 22 1/2" (49.5 cm × 45.7 cm × 57.2 cm)
Total	487 lb. (221 kg)	648 lb. (294 kg) ²	
Hardware			
Included hardware			
SBID 8070i-G4	SMART Board 8070i-G4 interactive flat panel (×2)		
AM70-L	Lync appliance		
CP311	Console		
CAM301	Camera		
MIC500	Table microphone (×2)		
MIX500	Audio processor		
CSR500	Speakers		
WM-SBID-501	Wall mount for installing an interactive flat panel on a wall (×2)		
Included cables			
For interactive flat panels	8' (2.4 m) IEC 60320 C13 to country-specific power (×2) 20' 8" (6.3 m) HDMI 16' 5" (5 m) USB		
For console	20' 8" (6.3 m) HDMI and USB 8' (2.4 m) IEC 60320 C13 to country-specific power 5' 4" (1.6 m) AC/DC converter		
For camera	9' 10" (3 m) USB Power		
Fankalda satasan b	201 (0)		

and audio processor

 $^{^2 \}mbox{lncluding the pallet}$

For speakers 6' (1.8 m) dual RCA

1' 7" (0.5 m) 3.5 mm Stereo to dual RCA 16' 5" (5 m) audio (speaker to speaker)

Power

For laptop³ 30' 6" (9.3 m) harness (HDMI and VGA)

Recommended diameter for conduit

13/4" (4.5 cm)

Interactive flat panels

Touch technology DViT® (Digital Vision Touch) technology

Screen size (diagonal) 70" (178 cm)

Aspect ratio 16:9

Optimal resolution 1920 × 1080 at 60 Hz

Horizontal frequency 54–69.75 kHz (analog and digital)

Vertical frequency 48–62 Hz

Contrast ratio (typical) 4000:1

Brightness (typical) 180–250 cd/m²

Pixel pitch 0.807 mm

Lync appliance

Processor 2.3 GHz Intel® Core™ i7 with HD 4000 graphics chipset

RAM Dual-channel 8 GB DDR3

Console

Screen size (diagonal) 11 5/8" (29.5 cm)

Aspect ratio 16:9

Resolution 1366×768

Brightness 250 cd/m²

Camera

Features Digital pan, tilt and zoom (DPTZ)

Automatic white balance

Automatic exposure and power line frequency detection

Manual lens tilt adjustment Internal privacy shutter Video recording indicator

Aspect ratio 16:9

Resolution (maximum) 1920 × 1080

Frame rate (typical) 30 frames per second (at \geq 200 lx)

³Laptop not included

SPECIFICATIONS

SMART ROOM SYSTEM FOR MICROSOFT LYNC FOR LARGE ROOMS - MODEL SRS-LYNC-L

Field of view 109° (full)

98° (horizontal)

Depth of field

3'-33' (1-10 m)

Signal-to-noise ratio

(minimum)

33 dB at ≥ 50 lx 36 dB at ≥ 200 lx

Dynamic range

(minimum)

42 dB

Table microphones

Features Mute button and indicator

> 13' (4 m) cable between microphones Daisy-chain up to five microphones

Local speaker audio

level

60-65 dBA measured at 20" (0.5 m)

Speakers

Total harmonic distortion

< 1% average < 3% maximum 80-10 kHz

Frequency response

 \pm 6 dB, 80–10 kHz

Nominal volume

76 dBSPL

Audio

Echo cancellation

> 45 dB at nominal receive output level

Software

Lync Room System

See lync.microsoft.com

software

Storage and operating requirements

Room system power (excluding console)

9.5A at 100V to 4A at 240V AC, 50 Hz to 60 Hz Power requirements

Power consumption at 950 W

77°F (25°C)

Console power

Normal power < 12 W (using the supplied 12 V AC/DC converter)

consumption

Standby power consumption

< 0.6 W

Storage

Temperature -4–140°F (-20–60°C)

Humidity 5–95% relative humidity, non-condensing

Operating

Temperature $41-95^{\circ}F$ (5-35°C)

Humidity 10–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification ⁴ UL (U.S. and Canada), FCC, IC, C-Tick, NOM, CU, CB, VCCI, KC, CCC, PSB, BIS, PSE, KCC

Environmental compliance

China EIP

European Union REACH, RoHS, WEEE, Battery and Packaging

U.S. Packaging and Conflict Minerals

Purchasing information

Order number

SRS-LYNC-L SMART Room System for Lync for large rooms

Optional accessories

MIC500 Additional table microphone

WSK-DUAL Wall stand kit for rooms with two interactive flat panels, including two wall stands for transferring

some of the weight of the interactive flat panels to the floor, and one cable raceway

 $^{^4\}mathrm{As}$ applicable to the components

SPECIFICATIONS

SMART ROOM SYSTEM FOR MICROSOFT LYNC FOR LARGE ROOMS - MODEL SRS-LYNC-L

Warranty

Two-year warranty Interactive flat panels

Camera

Lync appliance

I/O extension module

Console

One-year warranty Speakers

Wall mounts

90-day return Cables, pens, batteries and other items that can be purchased from the SMART Parts Store

(see smarttech.com/Support/PartsStore)

smarttech.com/support smarttech.com/contactsupport

© 2013–2014 SMART Technologies ULC. All rights reserved. SMART Room System, SMART Board, DVIT, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Microsoft, Lync and PowerPoint are either registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof covered by one or more of the following U.S. patients. www.smarttech.com/patents. Contents are subject to change without notice. 03/2014.