

Specifications

SMART Board® 7086 interactive display with iQ and Intel® Compute Card

Model SBID-7386

Overview

The SMART Board® 7086 interactive display with iQ and Intel® Compute Card is the hub of your classroom. iQ technology connects devices, lesson content and pedagogically relevant software to create a cohesive educational experience. PC-free embedded computing provides one-touch access to a diverse suite of SMART applications—Notebook lessons, workspaces, gamification activities and whiteboard—and collaborative tools, such as wireless screen sharing and a web browser. With minimal network integration, there's no need for wires, cables or manual software and firmware updates.



Install an Intel Compute Card in the appliance to provide a complete Windows® 10 solution at your fingertips. Choose from three compute card options to provide a consistent room-to-room Windows Full HD experience.

The 86" 4K ultra-high-definition LED display provides optimal image clarity and wide viewing angles. With the Pen ID™ feature, you can assign different appearances to the four pens and write or draw over any application in digital ink.

Object Awareness[™] allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and four users can write or draw at the same time.


See education.smarttech.com for more information.



As an ENERGY STAR® certified signage display, the SMART Board 7086 interactive display meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

Dimensions and weights¹

Dimensions



Weight

205 lb. (91 kg)

Shipping dimensions (including pallet)

86 1/2" × 60" × 14"

(220 cm × 163 cm × 35.5 cm)

Shipping weight

258 lb. (117 kg)

Hardware

Interaction

Touch technology	HyPr Touch™ (Hybrid Precision Touch) proprietary hybrid system, which greatly improves upon its InGlass™ core by optimizing both touch and pen performance, resulting in virtually no lag and zero contact detect height
Multitouch capabilities	Up to 16 simultaneous interaction points (combination of 10 finger touch points, four pen touch points and two eraser touch points) 2
Object Awareness	Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger, eraser, or palm.
Pen ID	Four people can write independently and simultaneously, using different colored ink.
Display	
Туре	LED
Aspect ratio	16:9
Optimal resolution ("HDMI 1" input)	4K UHD (3840 × 2160) at 60 Hz
Horizontal frequency (typical)	135 kHz
Vertical frequency (typical)	60 Hz

 $^{^{1}}$ All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

 $^{^2\}textsc{Only}$ up to 10 touch points and no pen or eraser support on Chrome $\textsc{OS}^{\tiny{\text{IM}}}$ operating system

Contrast ratio (typical) 5000:1

Brightness (maximum) 360 cd/m²

Pixel dimensions $0.429 \text{ mm} \times 0.429 \text{ mm}$

Gamut 72% of NTSC

Viewing angle 178°

Response time (typical) 8 ms

100BASE-T Ethernet Two external ports for a four-port Fast Ethernet switched network connecting the interactive

display and the iQ appliance to an external network and an external device, such as a computer

Presence detection Dual sensors that reduce startup time and power consumption during inactivity

Audio 10 W integrated speakers (×2)

Noise level <30 dBA

Included cables and iQ a

accessories

iQ appliance Intel Compute Card

Country-specific power cable

USB cable Pen (×4) Eraser

iQ appliance

Wi-Fi IEEE 802.11A/B/G/N/Ac with 2 × 2 MIMO (both 2.4 and 5 GHz bands)

Bluetooth® Bluetooth 4.2 dual mode (backwards compatible with Bluetooth 2.1 + EDR)

Capture options Establish a Bluetooth wireless connection with a supported mobile device (see below) by

scanning the interactive display's unique QR code

Intel Compute Card

features

 ${\it See iQ appliance with Intel Compute Card for SMART Board interactive displays specifications}$

(smarttech.com/kb/171263)

SMART BOARD 7086 INTERACTIVE DISPLAY WITH IQ AND INTEL COMPUTE CARD - MODEL SBID-7386

Supported languages Danish

Dutch
English
Finnish
French
German
Italian
Korean
Norwegian
Portuguese
Russian

Simplified Chinese

Spanish Swedish

Traditional Chinese

Ukrainian Vietnamese

Mounting holes For a standard VESA 600 mm × 400 mm mounting plate

Lower mounting holes 17 1/8" (43.4 cm) from the bottom of the interactive display

Mounting bracket depth Minimum depth of 2" (5.1 cm) for all components on the back of the interactive display for airflow

Connectors

Connector panel OPS slot (for the iQ appliance)

Stereo 3.5 mm out

S/PDIF out

"VGA" input connectors
Video: VGA in (1080p)
Audio: Stereo 3.5 mm in
Touch: USB Type-B
"HDMI 1" input connectors

Video/audio: HDMI 2.0 in (4K UHD at 60 Hz)

Touch: USB Type-B

"Display Port" input connectors
Video/audio: in (4K UHD at 30 Hz)

Touch: USB Type-B

USB Type-A³ RJ45 (×2)

Convenience panel "HD

"HDMI 2" input connectors

Video/audio: HDMI 1.4 in (4K UHD at 30 Hz)

Touch: USB Type-B USB Type-A (×2)

³For service use only

Bottom AC power in

AC power out RS-232 in RS-232 out

HDCP support Version 1.4/2.2

Installation requirements

Interactive display

See the SMART Board 7000 and 7000 Pro series interactive displays installation and maintenance guide (smarttech.com/kb/171164)

IMPORTANT

The display needs an internet connection for downloading and installing important updates. Ask the network administrator to confirm that the network has been correctly configured for the iQ experience. For more information about network configuration, see Connecting a SMART display with the iQ experience to a network.

SMART Notebook Player mobile app

SMART Notebook Player iOS 10 or later operating system software

SMART kapp® app

Apple devices iOS 9 or later operating system software

50 MB of storage iPhone 4S or later

Third-generation iPad or later First-generation iPad mini or later Fifth-generation iPod touch or later

Android™ devices

Android 4.4.4 (KitKat) or later operating system

50 MB of storage (internal or SD card)

1024 MB of RAM

720p or better screen resolution

Bluetooth 2.1 + EDR

3 megapixel or better rear-facing camera (recommended)

SMART kapp viewer

Mobile Safari for iOS 9 or later operating system software

Chrome[™] for Android 39.0.2171.93 or later

Desktop Internet Explorer® 10 or later

Chrome 39.0.2171.95 or later Firefox® 34.0.5 or later Safari 8.0 or later

Room computers and guest laptops

General requirements See SMART Notebook software release notes

4K UHD Video card that can support 3840 × 2160 resolution at 60 Hz and that has 1 GB DDR 5 memory

See Minimum requirements for Ultra High Definition or 4K on your interactive flat panel

Mini-computers

General requirements See SMART Notebook software release notes

Dimensions Smaller than $10" \times 10" \times 2"$ (25.4 cm \times 25.4 cm \times 5.1 cm)

Weight Less than 10 lb. (4.5 kg)

Mounting VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

Cable requirements

HDMI Maximum length: 23' (7 m)

NOTES

• Use only certified HDMI cables that have been tested to support the performance standard you require.

 The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.

Display Port Display Port 1.2 compliant or better

Maximum length: 23' (7 m)

USB 2.0 USB 2.0 certified

Hi-Speed (480 Mbps) support Maximum length: 16' (5 m)

Important Using cables that exceed these maximum lengths can produce unexpected results, such as

degraded picture quality or USB connectivity. Refer to *Installation best practices for SMART products* (smarttech.com/kb/171035) for comprehensive information about cables and

extensions for SMART hardware products.

Storage and operating requirements

Power requirements 100V to 240V AC, 50 Hz to 60 Hz

Interactive display and iQ appliance power consumption at 77°F (25°C)

Standby mode <17 W

Normal operating 174 W

Standalone interactive display power consumption at 77°F (25°C)

Standby mode <2 W

Normal operating 159 W

Operating temperature 41–95°F (5–35°C)

Storage temperature -4-140°F (-20-60°C)

Humidity 5–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification EU RED and LV Directives, ISED, cUL, FCC, UL, RCM, CITIC, TRA

Environmental compliance

European Union REACH, RoHS, WEEE, Battery and Packaging

U.S. CONEG Packaging, California Prop 65

Purchasing information

Order numbers

SBID-7386-PENT	SMART Board 7086 interactive display with iQ, Intel Compute Card (with Pentium® N4200 processor) and SMART Learning Suite
SBID-7386-M3	SMART Board 7086 interactive display with iQ, Intel Compute Card (with Intel Core™ m3-7Y30 processor) and SMART Learning Suite
SBID-7386-I5	SMART Board 7086 interactive display with iQ, Intel Compute Card (with Intel Core i5-7Y57 processor) and SMART Learning Suite
Optional accessories	See smarttech.com/accessories
Warranty	Three-year limited equipment warranty
Extended warranty	
EWY1-SBID-7386	One-year warranty extension
EWY2-SBID-7386	Two-year warranty extension

smarttech.com/support smarttech.com/contactsupport

^{© 2018–2019} SMART Technologies ULC. All rights reserved. SMART Board, SMART kapp, Pen ID, Object Awareness, HyPr Touch, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Intel, Pentium and Core are trademarks of Intel Corporation in the U.S. and/or other countries. iPhone, iPad, iPod touch and Safari are trademarks of Apple Inc., registered in the U.S. and other countries. Google Play, Android and Chrome are trademarks of Google Inc. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. November 14, 2019.